


## EPR/CN/XLPE Power, MV-105 Type Primary UD, 15kV 133% Single Conductor Un-Filled Copper - Silicone Free

### DESCRIPTION

The Medium Voltage Underground Distribution (UD) cables consist of a copper un-filled conductor, covered with ethylene propylene rubber (EPR), a concentric neutral of helically applied copper wires, and a moisture blocked cross-linked polyethylene (XLPE) jacket with 3 extruded red stripes.

### APPLICATIONS

- Suitable for underground primary power applications: direct burial or in duct.
- For wet or dry locations.
- Jacket is sunlight resistant.
- Excellent resistance to treeing
- Designed to operate continuously at a conductor temperature not exceeding
  - » 105°C for normal operations
  - » 140°C for emergency overload
  - » 250°C for short circuit



**SERIES U15BEX**

### CONSTRUCTION

<b>CONDUCTOR</b>	Fully annealed bare copper (filled) Class B compact strand
<b>STRAND SHIELD</b>	Extruded thermoset semi-conducting polymer over the conductor
<b>INSULATION</b>	Ethylene propylene rubber (EPR)
<b>INSULATION SHIELD</b>	Extruded thermoset semi-conducting polymer over the insulation
<b>SHIELD</b>	Helically applied, annealed, solid bare copper wires Reduced wire number per ICEA P-45-482 calculations
<b>JACKET</b>	Moisture blocked cross-linked polyethylene (XLPE)
<b>JACKET MARKING</b>	00000 FT LS CABLE XXXKCMIL (or AWG) CU CMPCT 1/C 15KV 133% INSUL LEVEL 220 MILS EPR 'No. of Neutral' X # 'Neutral size' MB XLPE JKT MV-105 (UL) MADE IN USA MM/DD/YYYY (LIGHTNING BOLT SYMBOL)
<b>PACKING</b>	Non-returnable wood reels

### STANDARDS (Compliance)

<b>PERFORMANCE</b>	AEIC CS8 ASTM B3 ASTM B496 ICEA S-94-649 ICEA T-34-664 UL 1072
<b>OTHER</b>	OSHA

## EPR/CN/XLPE Power, MV-105 Type Primary UD, 15kV 133% Single Conductor Un-Filled Copper - Silicone Free

SPECIFICATIONS							
Part Number	Conductor Size (AWG/kcmil)	Conductor Diameter (in)	Insulation Diameter (in)	Concentric Neutral (No. x AWG)	Jacket Thickness (in)	Approx. O.D (in)	Approx. Weight (lbs/kft)
U15BEX-1ACT-1CZ-R3Z-M	1/0	0.336	0.83	6 x 14 (1/3N)	0.050	1.16	820

The dimensions and weights shown are approximate and subject to industry standards. Other designs available upon request.