


TR-XLPE/CN/XLPE Power, MV-105 Type Primary UD, 35kV 100% Single Conductor Filled Aluminum - Silicone Free

DESCRIPTION

The Medium Voltage Underground Distribution (UD) cables consist of an aluminum filled conductor, covered with tree-retardant cross-linked polyethylene (TR-XLPE), a concentric neutral of helically applied copper wires, and a moisture blocked cross-linked polyethylene (XLPE) jacket with 3 extruded red stripes.

APPLICATIONS

- Suitable for underground primary power applications: direct burial or in duct.
- For wet or dry locations.
- Jacket is sunlight resistant.
- Excellent resistance to treeing
- Designed to operate continuously at a conductor temperature not exceeding
 - » 105°C for normal operations
 - » 140°C for emergency overload
 - » 250°C for short circuit



SERIES U35ATX

CONSTRUCTION

CONDUCTOR	Aluminum 1350 (filled) Class B compressed strand
STRAND SHIELD	Extruded thermoset semi-conducting polymer over the conductor
INSULATION	Tree-retardant cross-linked polyethylene (TR-XLPE)
INSULATION SHIELD	Extruded thermoset semi-conducting polymer over the insulation
SHIELD	Helically applied, annealed, solid bare copper wires Reduced wire number per ICEA P-45-482 calculations
JACKET	Moisture blocked cross-linked polyethylene (XLPE)
JACKET MARKING	00000 FT LS CABLE XXXKCMIL (or AWG) FS AL 1/C 35KV 100% INSUL LEVEL 345 MILS TRXLPE 'No. of Neutral' X # 'Neutral size' MB XLPE JKT MV-105 (UL) MADE IN USA MM/DD/YYYY (LIGHTNING BOLT SYMBOL)
PACKING	Non-returnable wood reels

STANDARDS (Compliance)

PERFORMANCE	AEIC CS8 ASTM B3 ASTM B230 ASTM B231 ICEA S-94-649 ICEA T-34-664 UL 1072
OTHER	OSHA

TR-XLPE/CN/XLPE Power, MV-105 Type Primary UD, 35kV 100% Single Conductor Filled Aluminum - Silicone Free

SPECIFICATIONS							
Part Number	Conductor Size (AWG/kcmil)	Conductor Diameter (in)	Insulation Diameter (in)	Concentric Neutral (No. x AWG)	Jacket Thickness (in)	Approx. O.D (in)	Approx. Weight (lbs/kft)
U35ATX-4AFB-1CZ-RQB-M	4/0	0.512	1.27	20 x 12 AWG (Custom)	0.050	1.65	1,340
U35ATX-35FB-1CZ-RQB-M	350	0.661	1.43	18 x 14 AWG (Custom)	0.075	1.83	1,440
U35ATX-50FB-1CZ-RQB-M	500	0.789	1.56	13 x 14 AWG (Custom)	0.075	1.96	1,615
U35ATX-75FB-1CZ-RQB-M	750	0.968	1.75	19 x 14 AWG (Custom)	0.075	2.18	2,115
U35ATX-A1FB-1CZ-RQB-M	1000	1.117	1.91	16 x 12 AWG (Custom)	0.075	2.37	2,590

The dimensions and weights shown are approximate and subject to industry standards. Other designs available upon request.