


TR-XLPE/CN/XLPE Power, MV-105 Type Primary UD, 35kV 100% Single Conductor Un-Filled Aluminum - Silicone Free

DESCRIPTION

The Medium Voltage Underground Distribution (UD) cables consist of an aluminum un-filled conductor, covered with tree-retardant cross-linked polyethylene (TR-XLPE), a concentric neutral of helically applied copper wires, and a cross-linked polyethylene (XLPE) jacket with 3 extruded red stripes.

APPLICATIONS

- Suitable for underground primary power applications: direct burial or in duct.
- For wet or dry locations.
- Jacket is sunlight resistant.
- Excellent resistance to treeing
- Designed to operate continuously at a conductor temperature not exceeding
 - » 105°C for normal operations
 - » 140°C for emergency overload
 - » 250°C for short circuit



SERIES U35ATX

CONSTRUCTION

CONDUCTOR	Aluminum 1350 (unfilled) Class B compressed strand
STRAND SHIELD	Extruded thermoset semi-conducting polymer over the conductor
INSULATION	Tree-retardant cross-linked polyethylene (TR-XLPE)
INSULATION SHIELD	Extruded thermoset semi-conducting polymer over the insulation
SHIELD	Helically applied, annealed, solid bare copper wires Reduced wire number per ICEA P-45-482 calculations
JACKET	Cross-linked polyethylene (XLPE)
JACKET MARKING	00000 FT LS CABLE XXXKCMIL (or AWG) AL 1/C 35KV 100% INSUL LEVEL 345 MILS TRXLPE 'No. of Neutral' X # 'Neutral size' XLPE JKT MV-105 (UL) MADE IN USA MM/DD/YYYY (LIGHTNING BOLT SYMBOL)
PACKING	Non-returnable wood reels

STANDARDS (Compliance)

PERFORMANCE	AEIC CS8 ASTM B3 ASTM B230 ASTM B231 ICEA S-94-649 UL 1072
OTHER	OSHA

TR-XLPE/CN/XLPE Power, MV-105 Type Primary UD, 35kV 100% Single Conductor Un-Filled Aluminum - Silicone Free

SPECIFICATIONS							
Part Number	Conductor Size (AWG/kcmil)	Conductor Diameter (in)	Insulation Diameter (in)	Concentric Neutral (No. x AWG)	Jacket Thickness (in)	Approx. O.D (in)	Approx. Weight (lbs/kft)
U35ATX-1AAB-1CZ-R2Z-Z	1/0	0.362	1.12	6 x 14 (1/2N)	0.050	1.46	795
U35ATX-4AAB-1CZ-R2Z-Z	4/0	0.512	1.27	11 x 14 (1/2N)	0.050	1.62	1,055
U35ATX-35AB-1CZ-R3Z-Z	350	0.661	1.43	13 x 14 (1/3N)	0.075	1.83	1,375
U35ATX-50AB-1CZ-R3Z-Z	500	0.789	1.56	18 x 14 (1/3N)	0.075	1.96	1,670
U35ATX-75AB-1CZ-R3Z-Z	750	0.968	1.75	26 x 14 (1/3N)	0.075	2.18	2,190
U35ATX-A1AB-1CZ-R3Z-Z	1000	1.117	1.91	23 x 12 (1/3N)	0.075	2.37	2,710
U35ATX-A2AB-1CZ-R6Z-Z	1250 ¹	1.250	2.05	23 x 14 (1/6N)	0.075	2.48	2,850
U35ATX-A5AB-1CZ-R6Z-Z	1500	1.370	2.17	26 x 14 (1/6N)	0.075	2.60	3,185

The dimensions and weights shown are approximate and subject to industry standards. Other designs available upon request.

¹1250 KCMIL may have 61 wires subject to mutual agreement between the manufacturer and customer per ASTM B231.